

| | | |
|--|--|--|
| <p>Art.-Nr.: 789.55 789.56 789.57 789.58 789.59 789.60</p> <p>PLIR 06/18</p> | <p>789.55_789.58</p> <p>1x</p> <p>1x</p> <p>1x</p> | <p>789.56_789.57_789.59_789.60</p> <p>1x</p> <p>1x</p> <p>1x</p> |
| | | |

A

789.55_789.58: driver 24VA

789.55_789.58: 1.5m

83mm

789.56_789.59: driver 48VA
789.57_789.60: driver 60VA

789.56_789.59: 3m
789.57_789.60: 5m

83mm

B

C

$r \geq 30\text{mm}$ $a \geq 60^\circ$

$r < 30\text{mm}$ $a < 60^\circ$

D

789.55_789.58

789.56_789.57_789.59_789.60

E

| | | | | | | | | |
|--------|-------|-----|-------|-----|-------|-----|-------|------|
| ON/OFF | | | | | | | | |
| | 1x | 2x | | | | | | |
| LIGHT | | | | | | | | |
| | 12.5% | 25% | 37.5% | 50% | 62.5% | 75% | 87.5% | 100% |
| | 1x | 2x | 3x | 4x | 5x | 6x | 7x | 8x |