

Farbe / colour:

Nr. 21

hellgrau / grey

12 Kartuschen a 300 ml



PCI
PCI Nanosil

**Elastischer Fugendichtstoff
für Innen und Außen**

Gliscode: DSE 20



11/24 - 67915704

MADE IN GERMANY

Art.-Nr. 5912779



DE119/01
PCI Nanosil
EN 15651-1, -2, -3
0757, 0767,
24

Sealants for non-structural use in joints in buildings and pedestrian walkways **EN 15651-1:2012**, Type F EXT-INT-CC Sealants for facade elements, Class 20 LM, Conditioning: Method A, Substrate: Mortar M1 without Primer **EN 15651-2:2012** Type G-CC Sealants for glazing, Class 20 LM, Conditioning: Method A, Substrate: Glass without Primer **EN 15651-3:2012** Type S Sealants for sanitary joints, Class XS1, Conditioning: Method A, Substrate: Glazed ceramic (EN 14411) Reaction to fire: Class E, Resistance to flow: ≤ 3 m, Loss of volume: ≤ 10 %, Tensile properties at maintained extension after immersion in water at 23 °C: Pass, Microbiological growth: 0, Adhesion/cohesion properties after exposure to heat, water and artificial light: Pass, Elastic recovery: ≥ 60 %, Tensile properties at -30 °C: ≤ 0.9 MPa, Tensile properties at maintained extension at -30 °C: Pass, Durability: Pass

PCI Augsburg GmbH, Piccardstrasse 11, D-86159 Augsburg, www.pci-augsburg.eu

- (D)** Enthält Biozid n-Butyl-1,2-benzisothiazolin-3-on
- (F)** Contient le produit biocide 1,2-Benzisothiazolin-3- one de n-Butyle
- (NL)** Bevat biocide n-Butyl-1,2-Benzisothiazolin-3-one
- (I)** Contiene il biocida n-butyl-1,2-benzisothiazolin-3-one



Scatola - PAP 20 - raccolta carta.
Cartuccia - HDPE 2 - raccolta plastica.
Beccuccio - HDPE 2 - raccolta plastica.
Verifica le disposizioni del tuo Comune.

Untergrund
grundieren

Untergrund
ausgleichen

Untergrund
abdichten

Fliesen
kleben

Fliesen
verfügen

PCI Augsburg GmbH
Piccardstr. 11
86159 Augsburg
Tel. +49 821 5901-0

Sika Schweiz AG - VE PCI
Tüfenwies 16
CH-8048 Zürich
Tel. +41 58 436 21 21

Sika Nederland B.V.
Postbus 40390
3504 AD Utrecht
tel. +31 30 241 0120



* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

BUILDING TRUST

