

# Material Safety Data Sheet

According to 91/155 EEC

Printing date 17.05.2004

Reviewed on 17.05.2004

## 1 Identification of the substance/preparation and of the company/undertaking

### · Product details

· Trade name: **Auto Acrylic Spray**

· Application of the substance / the preparation **Lacquer**

### · Manufacturer/Supplier:

MOTIP DUPLI GmbH  
Industriestrasse 19  
D-74855 Haßmersheim

Tel.: +49/6266/75-0

· Further information obtainable from: **Abteilung Produktsicherheit**

· Information in case of emergency:

Tel.: +49 6266-75-310











Fax +49 6266-75-362

## 2 Composition/information on ingredients

### · Chemical characterization

· Description: Mixture of substances listed below with nonhazardous additions.

### · Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2	acetone  Xi,  F; R 11-36-66-67	25-50%
CAS: 106-97-8 EINECS: 203-448-7	butane (containing $\geq 0,1$ % butadiene (203-450-8))  F+; R 12	10-25%
CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether  F+; R 12	10-25%
CAS: 74-98-6 EINECS: 200-827-9	propane  F+; R 12	10-25%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R 10-66-67	2.5-10%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate  Xi; R 10-36	2.5-10%
CAS: 71-36-3 EINECS: 200-751-6	butan-1-ol  Xn; R 10-22-37/38-41-67	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene  Xn; R 10-20/21-38	$\leq 2.5\%$
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol  Xi,  F; R 11-36-67	$\leq 2.5\%$

· Additional information: For the wording of the listed risk phrases refer to section 16.

## 3 Hazards identification

### · Hazard description:



Xi Irritant

F+ Extremely flammable

### · Information concerning particular hazards for human and environment:

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.

(Contd. on page 2)

# Material Safety Data Sheet

## According to 91/155 EEC

Printing date 17.05.2004

Reviewed on 17.05.2004

**Trade name: Auto Acrylic Spray**

(Contd. of page 1)

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

Has a narcotizing effect.

R 12 Extremely flammable.

R 36 Irritating to eyes.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

### 4 First-aid measures

- **General information:** Take affected persons out into the fresh air.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

### 5 Fire-fighting measures

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**  
Water  
Water with full jet
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.

### 6 Accidental release measures

- **Person-related safety precautions:**  
Keep away from ignition sources.  
Ensure adequate ventilation  
Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**  
Dispose of the material collected according to regulations.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Additional information:** See Section 13 for disposal information.

GB

(Contd. on page 3)

# Material Safety Data Sheet

According to 91/155 EEC

Printing date 17.05.2004

Reviewed on 17.05.2004

Trade name: Auto Acrylic Spray

(Contd. of page 2)

## 7 Handling and storage

- **Handling:**
- **Information for safe handling:**  
Keep away from heat and direct sunlight.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Do not seal receptacle gas tight.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

### · Ingredients with limit values that require monitoring at the workplace:

#### 67-64-1 acetone

OES (Great Britain)	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm New, IOELV
---------------------	--

#### 106-97-8 butane (containing ≥0,1 % butadiene (203-450-8))

OES (Great Britain)	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm
---------------------	---

#### 115-10-6 dimethyl ether

OES (Great Britain)	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm Long-term value: 766 mg/m <sup>3</sup> , 400 ppm IOELV
---------------------	--

#### 74-98-6 propane

OES (Great Britain)	Asphyxiant
---------------------	------------

#### 123-86-4 n-butyl acetate

OES (Great Britain)	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
---------------------	---

#### 108-65-6 2-methoxy-1-methylethyl acetate

OES (Great Britain)	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm New, IOELV, Sk
---------------------	--

#### 71-36-3 butan-1-ol

OES (Great Britain)	Short-term value: 154 mg/m <sup>3</sup> , 50 ppm Sk
---------------------	--

#### 1330-20-7 xylene

OES (Great Britain)	Short-term value: 662 mg/m <sup>3</sup> , 150 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
---------------------	---

(Contd. on page 4)

# Material Safety Data Sheet

According to 91/155 EEC

Printing date 17.05.2004

Reviewed on 17.05.2004

Trade name: Auto Acrylic Spray

(Contd. of page 3)

**67-63-0 propan-2-ol**

OES (Great Britain) Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Do not eat, drink, smoke or sniff while working.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not required.
- **Protection of hands:**  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**  
Natural rubber, NR
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Light weight protective clothing

## 9 Physical and chemical properties

### · General Information

**Form:** Aerosol  
**Colour:** According to product specification  
**Odour:** Characteristic

### · Change in condition

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Ignition temperature:** 235°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

### · Explosion limits:

**Lower:** 1.5 Vol %

(Contd. on page 5)

GB

# Material Safety Data Sheet

According to 91/155 EEC

Printing date 17.05.2004

Reviewed on 17.05.2004

Trade name: Auto Acrylic Spray

(Contd. of page 4)

<b>Upper:</b>	18.6 Vol %
· <b>Vapour pressure at 20°C:</b>	8300 hPa
· <b>Density at 20°C:</b>	0.868 g/cm <sup>3</sup>
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	92.0 %
<b>VOC-EU</b>	53.0 %
	798.4 g/l
<b>VOC-USA</b>	0.92 kg/l / 7.67 lb/gal
· <b>Solids content:</b>	7.1 %

## 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

## 12 Ecological information

- **General notes:**
- Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
- Do not allow product to reach ground water, water course or sewage system, even in small quantities.
- Danger to drinking water if even extremely small quantities leak into the ground.

## 13 Disposal considerations

- **Product:**
- **Recommendation**
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.

### · European waste catalogue

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Non contaminated packagings may be recycled.

GB

(Contd. on page 6)

# Material Safety Data Sheet

According to 91/155 EEC

Printing date 17.05.2004

Reviewed on 17.05.2004

Trade name: Auto Acrylic Spray

(Contd. of page 5)

## 14 Transport information

### · Land transport ADR/RID (cross-border)



- ADR/RID class: 2 5F Gases.
- Danger code (Kemler): 20
- UN-Number: 1950
- Hazard label 2.1
- Description of goods: 1950 AEROSOLS

### · Maritime transport IMDG:



- IMDG Class: 2
- UN Number: 1950
- Label 2.1
- EMS Number: F-D,S-U
- Marine pollutant: No
- Proper shipping name: AEROSOLS

### · Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 2.1
- UN/ID Number: 1950
- Label 2.1
- Proper shipping name: AEROSOLS, flammable

## 15 Regulatory information

### · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

### · Code letter and hazard designation of product:



Xi Irritant  
F+ Extremely flammable

### · Risk phrases:

- 12 Extremely flammable.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

### · Safety phrases:

- 2 Keep out of the reach of children.
- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 25 Avoid contact with eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

(Contd. on page 7)

# Material Safety Data Sheet

## According to 91/155 EEC

Printing date 17.05.2004

Reviewed on 17.05.2004

**Trade name: Auto Acrylic Spray**

(Contd. of page 6)

- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 33 Take precautionary measures against static discharges.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste.
- 64 If swallowed, rinse mouth with water (only if the person is conscious).

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

· **National regulations:**

· **Information about limitation of use:** Employment restrictions concerning juveniles must be observed.

· **Technical instructions (air):**

Class	Share in %
NK	92.0

· **Waterhazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

- 10 Flammable.
- 11 Highly flammable.
- 12 Extremely flammable.
- 20/21 Harmful by inhalation and in contact with skin.
- 22 Harmful if swallowed.
- 36 Irritating to eyes.
- 37/38 Irritating to respiratory system and skin.
- 38 Irritating to skin.
- 41 Risk of serious damage to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Abteilung Labor/QS

· **Contact:**

Ernst Kast

Motip Dupli GmbH

· **\* Data compared to the previous version altered.**

GB