

Farbe / colour:

Nr. 21

hellgrau / grey

12 Kartuschen a 300 ml



**PCI**  
**PCI Nanosil**

**Elastischer Fugendichtstoff  
für Innen und Außen**

Gliscode: DSE 20



11/24 - 67915704

MADE IN GERMANY

Art.-Nr. 5912779



DE119/01  
PCI Nanosil  
EN 15651-1, -2, -3  
0757, 0757/  
24

Sealants for non-structural use in joints in buildings and pedestrian walkways **EN 15651-1:2012**, Type F EXT-INT-CC Sealants for facade elements, Class 20 LM, Conditioning: Method A, Substrate: Mortar M1 without Primer **EN 15651-2:2012** Type G-CC Sealants for glazing, Class 20 LM, Conditioning: Method A, Substrate: Glass without Primer **EN 15651-3:2012** Type S Sealants for sanitary joints, Class XS1, Conditioning: Method A, Substrate: Glazed ceramic (EN 14411) Reaction to fire: Class E, Resistance to flow:  $\leq 3$  m, Loss of volume:  $\leq 10$  %, Tensile properties at maintained extension after immersion in water at 23 °C: Pass, Microbiological growth: 0, Adhesion/cohesion properties after exposure to heat, water and artificial light: Pass, Elastic recovery:  $\geq 60$  %, Tensile properties at  $-30$  °C:  $\leq 0.9$  MPa, Tensile properties at maintained extension at  $-30$  °C: Pass, Durability: Pass

PCI Augsburg GmbH, Piccardstrasse 11, D-86159 Augsburg, [www.pci-augsburg.eu](http://www.pci-augsburg.eu)

**(D)** Enthält Biozid n-Butyl-1,2-benzisothiazolin-3-on

**(F)** Contient le produit biocide 1,2-Benzisothiazolin-3- one de n-Butyle

**(NL)** Bevat biocide n-Butyl-1,2-Benzisothiazolin-3-one

**(I)** Contiene il biocida n-butyl-1,2-benzisothiazolin-3-one



Scatola - PAP 20 - raccolta carta.  
Cartuccia - HDPE 2 - raccolta plastica.  
Beccuccio - HDPE 2 - raccolta plastica.  
Verifica le disposizioni del tuo Comune.

Untergrund  
grundieren

Untergrund  
ausgleichen

Untergrund  
abdichten

Fliesen  
kleben

Fliesen  
verfügen

PCI Augsburg GmbH  
Piccardstr. 11  
86159 Augsburg  
Tel. +49 821 5901-0

Sika Schweiz AG - VE PCI  
Tüfenwies 16  
CH-8048 Zürich  
Tel. +41 58 436 21 21

Sika Nederland B.V.  
Postbus 40390  
3504 AD Utrecht  
tel. +31 30 241 0120



\* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à E (fortes émissions).

BUILDING TRUST

